

# **Safety Data Sheet**

## Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-3042-5	Version Number:	29.00
Issue Date:	04/06/22	Supercedes Date:	05/26/21

# **SECTION 1: Identification**

## 1.1. Product identifier

3M<sup>™</sup> Novec<sup>™</sup> 72DE Engineered Fluid

## **Product Identification Numbers**

ID Number	UPC	ID Number	UPC
70-2134-0515-5		80-0014-2690-9	
98-0212-2966-5	00-51135-71036-4	98-0212-2967-3	00-51135-71037-1
98-0212-2968-1	00-51135-71038-8	98-0212-3162-0	00-51135-71601-4

4010039372, 7100037080, 7100035103, 7100026794, 7100189833, 7100260440

## 1.2. Recommended use and restrictions on use

## **Recommended use**

For Industrial Use Only. See Limitations on Use for supplemental information on intended applications including Medical Device applications.

## **Restrictions on use**

. . .

Novec<sup>™</sup> Engineered Fluids are used in a wide variety of applications including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec <sup>™</sup> solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration.

3M Electronics Materials Solutions Division (EMSD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMSD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Supplier's details	
<b>MANUFACTURER:</b>	3M
DIVISION:	Electronics Materials Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

\_\_\_\_\_

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

## 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B. Specific Target Organ Toxicity (single exposure): Category 3.

## 2.2. Label elements Signal word

Warning

Symbols Exclamation mark |

## Pictograms



Hazard Statements Causes eye irritation. May cause drowsiness or dizziness.

## **Precautionary Statements**

## **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling.

## **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.

## Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

## **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Hazards not otherwise classified

In use, may form flammable/explosive vapour-air mixture.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
1,2-Trans-dichloroethylene	156-60-5	68 - 72 Trade Secret *

<b>3M<sup>TM</sup></b> Novec <sup>TM</sup> 72DE Engineered Fluid 0	4/06/22
--	---------

Ethyl nonafluoroisobutyl ether	163702-06-5	10 - 20
Ethyl nonafluorobutyl ether	163702-05-4	1 - 10
Methyl nonafluoroisobutyl ether	163702-08-7	5 - 10
Methyl nonafluorobutyl ether	163702-07-6	1 - 5

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

## **Skin Contact:**

Wash with soap and water. If you feel unwell, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

## If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

## 5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition. Material displays no closed-cup flash point but may form flammable/explosive vapor air mixture.

## Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Fluoride	During Combustion

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sparks, flames, and extreme heat. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Eliminate all potential ignition sources when cleaning up spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Contents may be under pressure, open carefully. Do not breathe thermal decomposition products. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Keep away from sparks, flames, and extreme heat.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store at temperatures not exceeding 38C/100F Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
1,2-Trans-dichloroethylene	156-60-5	ACGIH	TWA:200 ppm	
Ethyl nonafluorobutyl ether	163702-05-	Manufacturer	TWA(as total isomers):200	
	4	determined	ppm(2160 mg/m3)	
Ethyl nonafluoroisobutyl ether	163702-06-	Manufacturer	TWA(as total isomers):200	
	5	determined	ppm(2160 mg/m3)	
Methyl nonafluorobutyl ether	163702-07-	AIHA	TWA:750 ppm	
	6			
Methyl nonafluoroisobutyl ether	163702-08-	AIHA	TWA:750 ppm	
	7			

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

#### **Skin/hand protection**

Chemical protective gloves are not required under normal use conditions. However, when the product is subjected to extreme heat, HF may be formed. For those cases, neoprene gloves and apron are recommended.

#### **Respiratory protection**

Annoononoo

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Colorless
Specific Physical Form:	Liquid
Odor	Slight Odor
Odor threshold	No Data Available
рН	Not Applicable
Melting point	Not Applicable
Boiling Point	43 °C
Flash Point	No flash point [Details: Tested according to ASTM method D
	3278-96]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	7.3 % volume [ <i>Details:</i> @ 25 C, Tested according to ASTM method E-681-98 (per Annex A1)]

Flammable Limits(UEL)	15.0 % volume [ <i>Details:@</i> 25 C, Tested according to ASTM method E-681-98 (per Annex A1)]
Vapor Pressure	350  mmHg [@, 25 °C]
Vapor Density	No Data Available
Density	1.28 g/ml
Specific Gravity	1.28 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	396 °C
Decomposition temperature	Not Applicable
Viscosity	0.45 centipoise
Molecular weight	No Data Available
Volatile Organic Compounds	896 g/l [ <i>Test Method</i> :South Cost Air Qual Mgmt Dist]
Percent volatile	100 %
VOC Less H2O & Exempt Solvents	896 g/l [Test Method:calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid** Heat Sparks and/or flames

# **10.5. Incompatible materials** Strong bases

Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>	
Carbon monoxide	At Elevated Temperatures -	extreme conditions of
	heat	
Carbon dioxide	At Elevated Temperatures -	extreme conditions of
	heat	
Hydrogen Chloride	At Elevated Temperatures -	extreme conditions of
	heat	
Hydrogen Fluoride	At Elevated Temperatures -	extreme conditions of
	heat	
Perfluoroisobutylene (PFIB)	At Elevated Temperatures -	extreme conditions of
	heat	

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

## Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

## **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

## **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

## Additional Health Effects:

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor (4 hours)	Rat	LC50 > 19.7 mg/l
1,2-Trans-dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,2-Trans-dichloroethylene	Inhalation- Vapor (4 hours)	Rat	LC50 95.6 mg/l
1,2-Trans-dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Ethyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Ethyl nonafluoroisobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 989 mg/l
Ethyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 2,000 mg/kg

Ethyl nonafluorobutyl ether	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Methyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethyl nonafluorobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 989 mg/l
Ethyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 2,000 mg/kg
Methyl nonafluoroisobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl nonafluorobutyl ether	Dermal		LD50 estimated to be > 5,000 mg/kg
Methyl nonafluorobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
1,2-Trans-dichloroethylene	Rabbit	Minimal irritation
Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation

## Serious Eye Damage/Irritation

Name	Species	Value
1,2-Trans-dichloroethylene	Rabbit	Moderate irritant
Ethyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Ethyl nonafluorobutyl ether	Rabbit	No significant irritation
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation

## **Skin Sensitization**

Name	Species	Value
Ethyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Ethyl nonafluorobutyl ether	Guinea	Not classified
	pig	
Methyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Methyl nonafluorobutyl ether	Guinea	Not classified
	pig	

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Germ Cell Mutagenicity

Name	Route	Value
1,2-Trans-dichloroethylene	In Vitro	Not mutagenic
1,2-Trans-dichloroethylene	In vivo	Not mutagenic
Ethyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Ethyl nonafluorobutyl ether	In Vitro	Not mutagenic
Ethyl nonafluorobutyl ether	In vivo	Not mutagenic
Methyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Methyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Methyl nonafluorobutyl ether	In Vitro	Not mutagenic
Methyl nonafluorobutyl ether	In vivo	Not mutagenic

## Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

## **Reproductive Toxicity**

## **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
1,2-Trans-dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesi s
Ethyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Ethyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 260 mg/l	during gestation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Methyl nonafluorobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,2-Trans-dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2-Trans-dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1,2-Trans-dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable
Ethyl nonafluoroisobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluoroisobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
Ethyl nonafluorobutyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 204 mg/l	17 minutes
Ethyl nonafluorobutyl ether	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 989 mg/l	4 hours
Methyl nonafluoroisobutyl ether	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Methyl nonafluoroisobutyl ether	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913 mg/l	10 minutes
Methyl nonafluorobutyl ether	Inhalation	nervous system	Not classified	Dog	LOAEL 913 mg/l	10 minutes
Methyl nonafluorobutyl ether	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913 mg/l	10 minutes

## Specific Target Organ Toxicity - repeated exposure

Name Route Target Organ(s) Value Species Test Rest	t Exposure Duration
--	------------------------

1,2-Trans-dichloroethylene	Inhalation	endocrine system   liver   kidney and/or	Not classified	Rat	NOAEL 16 mg/l	90 days
10 Trans dials di l	Incost	bladder   respiratory system	N-4-1:::		NOAF	14 1
1,2-Trans-dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
1,2-Trans-dichloroethylene	Ingestion	blood   liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks
1,2-Trans-dichloroethylene	Ingestion	heart   immune system   respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Ethyl nonafluoroisobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Ethyl nonafluoroisobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Ethyl nonafluorobutyl ether	Inhalation	liver   kidney and/or bladder   respiratory system   heart   endocrine system   gastrointestinal tract   bone marrow   hematopoietic system   immune system   nervous system	Not classified	Rat	NOAEL 263.4 mg/l	4 weeks
Ethyl nonafluorobutyl ether	Ingestion	blood   liver   kidney and/or bladder   heart   endocrine system   bone marrow   hematopoietic system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methyl nonafluoroisobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluoroisobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Ingestion	endocrine system   liver   heart	Not classified	Rat	NOAEL 1,000	28 days

		hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system		D (	mg/kg/day	12
Methyl nonafluorobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluorobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluorobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluorobutyl ether	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

## **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## **15.1. US Federal Regulations**

Contact 3M for more information.

## EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards	
Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	

## This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	<u>C.A.S. No</u>	<b><u>Regulation</u></b>	<u>Status</u>
1,2-Trans-dichloroethylene	156-60-5	Toxic Substances Control Act (TSCA) 4	Applicable
		Test Rule Chemicals	

## **15.2. State Regulations**

Contact 3M for more information.

## **15.3.** Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## **15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

## NFPA Hazard Classification Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride and Perfluoroisobutylene (PFIB). During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

## **HMIS Hazard Classification**

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	16-3042-5	Version Number:	29.00
Issue Date:	04/06/22	Supercedes Date:	05/26/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

## 3M USA SDSs are available at www.3M.com