

Elite Sil CN60E

- Low dosage
- Low VOC
- Easy to use
- Environmentally friendly

Rev. No. 05/2023

SPECIFICATIONS

Elite Sil CN60E is a special emulsion of silane / siloxane composite, which can be integrated into the mortar for waterproofing. And Surface coating on the surface of the substrate can produce a good hydrophobic effect.

PHYSICAL PROPERTY

Properties	Result
Active Ingredients	50-52 %
Appearance	Milky white liquid
Chemical content	Silane/Siloxane composite
Specific Gravity at 25 °C	0.90-1.00
pH value	6.0-8.0

RECOMMENDED WAY of USAGE

1. It is recommended to use 0.05-0.4% of the whole weight cement-based products. Generally, 0.2% can produce excellent results.

When used as surface waterproofing treatment

1. It recommended an active substance content of 5-10 (dilute the product in the ratio 1:4 to 1:9), the exact figure depending on how absorbent the substrate is. Brush or spray the substrate, make substrate fully wet. After the construction, substrate need 2~3 days protection ensures to silicone resin fully cured.

PRICE

Contact to sales representative

The information contained in this Technical Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Organic Wealth (Thailand) Co., Ltd believes to be reliable, however we make no representation or warranty as to the completeness or accuracy thereof and we assume no

liability resulting from its use or for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgment as to the appropriateness of its use, and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use

Technical Data Sheet